

THE ENVIRONMENTALLY FRIENDLY WATERSHIELD DROP MONITORS WATER USE AND REGENERATES ONLY WHEN NECESSARY. CONSERVING SALT, WATER, AND ELECTRICITY.

ROBUST FLOW RATES OF UP TO 27 GALLONS PER MINUTE OF
CONDITIONED WATER ARE AVAILABLE FROM THE WATERSHIELD DROP.
PROVIDING FOR THE SOFT, REFINED WATER DEMANDS OF TODAY'S
LARGER HOMES.

ENVIRONMENTALLY HARDENED SOLID STATE MICROPROCESSOR TECHNOLOGY ALLOWS THE WATERSHIELD DROP TO BE INSTALLED INSIDE OR OUT (NON FREEZING ENVIRONMENTS). SYSTEM CONFIGURTION AND OPERATIONAL DATA IS KEPT IN NON VOLATILE MEMORY. TIME OF DAY PICKS UP WHERE IT WAS PRIOR TO POWER INTERRUPTIONS.

A DOUBLE BACKWASH FEATURE OFFERS THE OPTIMUM IN REGENERTION, CLEANING ABILITY, AND EFFICIENCY.

COLOR SPECIFIC BACKLIGHT DISPLAYS SHOWS WHEN THE VALVE IS IN SERVICE, REGENERATION, OR IN ERROR STATE.



